


DETAILED DIMENSIONS



RAILGATE SERIES

DOCK-FRIENDLY (RF) MODELS



	A	B	C	D	E	F	G	H	I	J	K
	Platform Loading Width	Clear Opening Between Uprights	Overall Platform Width	Frame Width Outside Uprights	Upright Height	Height of Upright Above Mainframe	Latchplate to Top of Mainframe	Top of Mainframe to Outrail Bottom	Stored Platform to Outrail Bottom	Self-Close Ramp to Outrail Bottom	Mainframe Top to Mainframe Bottom
85-XX RF 45-6	83-1/2	81	85	90-3/4	83-11/16	56-9/16	18-3/8	27-1/8	25-9/16	13-7/8	11-15/16
85-XX RF 45-12	83-1/2	81	85	90-3/4		56-9/16		27-1/8	25-9/16	13-7/8	11-15/16
85-XX RF 50-6	83-1/2	81	85	90-3/4		56-9/16		27-1/8	25-9/16	13-7/8	11-15/16
A85-XX RF 45-6	83-1/2	81	85	92-1/4		56-1/2		27-1/4	25-9/16	13-15/16	12-1/16
A85-XX RF 45-12	83-1/2	81	85	92-1/4		56-1/2		27-1/4	25-9/16	13-15/16	12-1/16
A85-XX RF 50-6	83-1/2	81	85	92-1/4		56-1/2		27-1/4	25-9/16	13-15/16	12-1/16
89-XX RF 45-6	87-1/2	85	89	94-3/4		56-9/16		27-1/8	25-9/16	13-7/8	11-15/16
89-XX RF 45-12	87-1/2	85	89	94-3/4		56-9/16		27-1/8	25-9/16	13-7/8	11-15/16
89-XX RF 50-6	87-1/2	85	89	94-3/4		56-9/16		27-1/8	25-9/16	13-7/8	11-15/16
A89-XX RF 45-6	87-1/2	85	89	96-1/4		56-1/2		27-1/4	25-9/16	13-15/16	12-1/16
A89-XX RF 45-12	87-1/2	85	89	96-1/4		56-1/2		27-1/4	25-9/16	13-15/16	12-1/16
A89-XX RF 50-6	87-1/2	85	89	96-1/4		56-1/2		27-1/4	25-9/16	13-15/16	12-1/16

*XX in the model number column denotes either capacity model number. Capacity does not affect physical dimensions.

** Maximum Truck Bed Height for all RF models is 52 inches.

*** Lifting Capacities for all RF models are 1600 & 2000 lbs.

