



RUGGED. RELIABLE. REAL.

ET8KX

FEATURES

- 3,200 LB Maximum Lifting Capacity
- 8,000 FT-LB Moment Rating
- Electric - Hydraulic Power
- Hydraulic Boom Extension 6-10 FT
- Manual Boom Extension 10-14 FT
- Continuous Power Rotation
- Meets ANSI B30.5 Safety Standards
- Meets OSHA 1910.180 Requirements

LIFTING CAPACITIES	
REACH (FT.)	CAPACITY (LBS.)
2.5	3,200
6	1,325
10	800
14	575

STANDARD EQUIPMENT

- Capacity Overload Shut-Off System
- Anti-Two-Blocking System
- 65 FT of 1/4" Aircraft-Quality Wire Rope
- Remote Control Pendant: 25 FT Cord and Quick Disconnect
- Load Block with Swivel Hook Safety Latch
- Master Disconnect Switch
- Battery Cable: 25 FT

MINIMUM REQUIREMENTS

- 8,000 LB GVWR Chassis
- Outriggers
- Electric Power Source: 12V DC

OPTIONAL EQUIPMENT

- Radio Remote Controls
- Electric/Hydraulic and Manual Outrigger Packages
- Mounting Pedestal for Platform Bodies
- Boom Rests
- Cable Overhaul Weight

