



RUGGED. RELIABLE. REAL.

CT310KX

FEATURES

- Slewing ring fixed – can be placed in tight spaces
- Rotation stop can be adjusted
- 59" height in stored position
- 1,900 LB Maximum Lifting Capacity
- 6,650 FT-LB moment rating
- Electric-Hydraulic Power
- High-Efficiency, Heavy-Duty Electric Planetary Winch
 - 26 ft/min at 0 LBS; 18ft/min at 1,000 LBS
 - 12V Permanent Magnet Motor
 - Dual load applied and dynamic braking system
 - High-efficiency 3-stage planetary geartrain (216:1)
- Hydraulic power boom extension to 6' 3"
- Manual boom extension to 9'3"
- Load-holding counterbalance valves on all cylinders
- Meets ANSI B30.5 Safety Standards
- Meets OSHA 1910.180 Requirements

STANDARD EQUIPMENT

- Remote Control Pendant: 20 Ft Cord with Quick Disconnect
- Audible overload alarm protection
- 50 FT of 3/16" Wire Rope
- Load block with swivel hook and safety latch
- Master Disconnect Switch
- Battery Cable: 25 Ft, 4-Gauge
- Weight: 474 - 497 LBS

LIFTING CAPACITIES	
REACH (FT.)	CAPACITY (LBS.)
4.5	1,900
7.25	1,000
9.25	700

